

Submersible Transformers

Power Partners Submersible Transformers feature a round vertical tank that is hermetically sealed for repeated flooding and/or immersion. Terminals, ground pads, and nameplates are cover-mounted for easy access from ground level. *Ratings 25-167 KVA Single Phase*

High Voltage 25kV 125 kV BIL and below

Low Voltage 600v 30 kV BIL and below

Standard Accessories:

- 304 stainless steel tank, cover and hardware
- Bushing wells for deadfront elbow connectors arranged for loop or radial feed
- Parking stand for loadbreak primary connector
- Low voltage stud type bushings with screw on cable leads or spades
- Liquid level indicator



Power Partners

In addition to standard accessories the following options are offered:

- 1 or 2 primary 2-position 200A loadbreak switches
- Externally replaceable full range current limiting fuse with interlock loadbreak switch
- Bayonet type fuse with isolation link or partial range underoil current limiting fuse
- Secondary breaker and coordinated internal primary fuse
- Grounded LV neutral with stainless steel spade terminal
- Loadbreak or non-loadbreak primary inserts
- Non-loadbreak parking stands
- Spades on low voltage bushings
- Automatic pressure relief device
- Taps or series multiple ratings
- Natural Ester Fluids

200 Newton Bridge Road
Athens, Georgia 30605

Phone: 706-548-3121

Fax: 706-548-1929

E-mail: info@powerpartners-usa.com



A SPIRE POWER SOLUTIONS COMPANY